

Project: Cooling the Aluminum Cylinder

Background: A solid aluminum cylinder treated as a lumped-mass¹ system is immersed in a bath of iced water. Let us develop the mathematical model for the problem. When the cylinder is placed in the iced water bath, the cylinder loses heat to its surroundings by convection.

$$\text{Rate of heat lost due to convection} = h(\theta)A(\theta - \theta_a). \quad (1)$$

where

$\theta(t)$ = temperature of aluminum cylinder as a function of time, °C

$h(\theta)$ = the convective cooling coefficient, W/(m²-°C)

A = surface area, m²

θ_a = ambient temperature of iced water, °C

The energy stored in the mass is given by

$$\text{Energy stored by mass} = mC\theta \quad (2)$$

where

m = mass of the trunnion, kg

C = specific heat of the cylinder, J/(kg-K)

From an energy balance,

$$\begin{aligned} \text{Rate at which heat is gained} - \text{Rate at which heat is lost} \\ = \text{Rate at which heat is stored} \end{aligned}$$

gives

$$-hA(\theta - \theta_a) = mC \frac{d\theta}{dt} \quad (3)$$

The ordinary differential equation is subjected to

$$\theta(0) = \theta_0$$

where

θ_0 = initial temperature of aluminum cylinder, °C

Assuming the convective cooling coefficient, h to be a constant function of temperature, the exact solution to the differential equation (3) is

$$\frac{\theta - \theta_a}{\theta_0 - \theta_a} = e^{-\frac{hAt}{mC}}$$

¹ It implies that the internal conduction in the trunnion is large enough that the temperature throughout the trunnion is uniform. This allows us to assume that the temperature is only a function of time and not of the location in the trunnion. This means that if a differential equation governs this physical problem, it would be an ordinary differential equation for a lumped system and a partial differential equation for a non-lumped system. In your heat transfer course, you will learn when a system can be considered lumped or non-lumped. In simplistic terms, this distinction is based on the material, geometry, and heat exchange factors of the ball with its surroundings.

What to do in the lab:

1. Fill the ice-cooler with half-water and half-ice. It is better to use the water from the water-cooler, as it is cooler than the tap water. Keep stirring the ice, so that ice cubes do not get stuck to each other.
2. Take the thermocouple wires and connect them properly (+ to +, - to -) to the temperature indicator. Two thermocouples are attached to illustrate the concept of a lumped system. See the question#10 of this handout and the relationship of a lumped-unlumped system to Biot's number.
3. Turn the temperature indicator on and wait for a few seconds to record the initial temperature of the cylinder.
4. Record the temperature of the iced-water using a temperature indicator.
5. Immerse the aluminum cylinder in a bath of iced water and start the stopwatch simultaneously. Every five to ten seconds, record the temperature of the cylinder as a function of time.



Figure 1. Cooling the Aluminum Cylinder

Exercises to do (100 points – This is equivalent of 2 projects):

First, follow the sample project guidelines.

Use Matlab to solve problems (3 thru 11). Use comments, display commands and fprintf statements, sensible variable names and units to explain your work. Staple all the work in the following sequence. **Use SI system of units throughout.**

1. Signed typed affidavit sheet.
2. On engineering graph paper, write the data of temperature vs. time we collected in class. Also, write the following data given to you.
Diameter of cylinder = 44.57 mm
Length of cylinder = 105.47 mm
Density of aluminum = 2700 kg/m³
Specific heat of aluminum = 901 J/(kg-°C)

Thermal conductivity of aluminum = 240 W/(m-K)

Table 1. Coefficient of thermal expansion vs. temperature for aluminum (Data taken from <http://www.llnl.gov/tid/lof/documents/pdf/322526.pdf> by using mid values of temperatures at which CTE is reported)

Temperature (°C)	Coefficient of thermal expansion (μm/m/°C)
-10	58
12.5	59
37.5	60
62.5	62
87.5	66
112.5	71

- Regress the temperature vs. time data to the model $\frac{\theta - \theta_a}{\theta_0 - \theta_a} = e^{-\frac{hAt}{mC}}$. Find the only unknown constant of the regression model, that is, h . See hint for finding h at the end of the document.
- Illustrate and plot the temperature vs time data that shows individual data points and the plot of the regression curve.
- Find the best estimate of the total reduction in the diameter of the solid cylinder when immersed in iced water for a long time.
- Find the best estimate of the rate at which heat is lost by the cylinder to the iced water at $t=11.8$ seconds.
- Find the best estimate of the rate of change of temperature with respect to time at $t=11.8$ seconds..
- Find the best estimate of the rate at which heat is stored in the cylinder at $t=11.8$ seconds..
- Find the best estimate of the time in seconds it will take for the cylinder to reach 1.05 times the steady state temperature.
- Is the assumption of the aluminum cylinder being considered as a lumped system correct? To determine whether a system is lumped, we calculate the *Biot* number, defined as

$$Bi = \frac{hL}{k_s}$$

where

h = average surface conductance (same as convective cooling coefficient)

L = significant length dimension (volume of body/surface area)

k_s = thermal conductivity of solid body

If $Bi < 0.1$, the system can be treated as a lumped system and the temperature will be uniform in the body within 5% error.

11. Using the value of h , obtained from problem#3, a) solve the differential equation (Eqn (3)) *analytically* using MATLAB, b) find the value of the temperature at $t=10$ seconds, c) find the relative percentage difference between the experimental (observed) and predicted values.

Hint for Problem#3

Given $(x_1, y_1), (x_2, y_2), \dots (x_n, y_n)$, best fit $y = e^{bx}$ to the data

A formula to find b in the regression formula is given below.

$$b = \frac{\sum_{i=1}^n x_i \ln(y_i)}{\sum_{i=1}^n x_i^2}$$

You can now use the for loops to find b . If you have found another way of regressing the data correctly in MATLAB, ignore my hint. If you are unable to find b , use whatever you think is the right way to do the problem. You may not be doing what is right though but it will allow you to solve the other questions.